## IEEE JOURNAL OF SOLID-STATE CIRCUITS

A PUBLICATION OF THE IEEE SOLID-STATE CIRCUITS SOCIETY



JANUARY 2016

VOLUME 51

NUMBER 1

IJSCBC

(ISSN 0018-9200)

## SPECIAL ISSUE ON THE 2015 IEEE INTERNATIONAL SOLID-STATE CIRCUITS CONFERENCE

A 16 nm All-Digital Auto-Calibrating Adaptive Clock Distribution for Supply Voltage Droop Tolerance Across a Wide	
Operating Range	
J. T. Bridges, D. J. Yingling, H. H. Nguyen, B. R. Appel, Y. N. Kolla, J. Jeong, F. I. Atallah, and D. W. Hansquine	8
Enabling Wide Autonomous DVFS in a 22 nm Graphics Execution Core Using a Digitally Controlled Fully Integrated	
Voltage Regulator	
R. Jain, J. F. Ryan, C. Tokunaga, C. Augustine, J. P. Kulkarni, K. Ravichandran, J. W. Tschanz, M. M. Khellah, and V. De	18
A Subthreshold ARM Cortex-M0+ Subsystem in 65nm CMOS for WSN Applications with 14 Power Domains, 10T	
SRAM and Integrated Voltage Regulator J. Myers, A. Savanth, R. Gaddh, D. Howard, P. Prabhat, and D. Flynn	31
A 2.71nJ/Pixel Gaze-Activated Object Recognition System for Low-power Mobile Smart Glasses	
I. Hong, K. Bong, D. Shin, S. Park, K. Jason Lee, Y. Kim, and HJ. Yoo	45
A 0.5 nJ/Pixel 4 K H.265/HEVC Codec LSI for Multi-Format Smartphone Applications	
CC. Ju, TM. Liu, KB. Lee, YC. Chang, HL. Chou, CM. Wang, TH. Wu, HM. Lin,	
YH. Huang, CY. Cheng, TA. Lin, CC. Chen, YK. Lin, MH. Chiu, WC. Li, SJ. Wang, YC. Lai, P. Chao,	
CD. Chien, MJ. Hu, PH. Wang, YC. Huang, SH. Chuang, LF. Chen, HY. Lin, ML. Wu, and CH. Chen	56
A Configurable 12-to-237kS/s 12.8mW Sparse-Approximation Engine for Mobile Data Aggregation of	
Compressively-Sampled Physiological Signals F. Ren, and D. Marković	68
SPARC M7: A 20 nm 32-Core 64 MB L3 Cache Processor G. K. Konstadinidis, H. Li, F. Schumacher,	
V. Krishnaswamy, H. Cho, S. Dash, R. Masleid, C. Zheng, Y. D. Lin, P. Loewenstein, H. Park, V. Srinivasan, D. Huang,	
C. Hwang, W. Hsu, C. McAllister, J. Brooks, H. Pham, S. Turullols, Y. Yanggong, R. Golla, A. P. Smith, and A. Vahidsafa	79
The Xeon® Processor E5-2600 v3: a 22 nm 18-Core Product Family	
B. Bowhill, B. Stackhouse, N. Nassif, Z. Yang, A. Raghavan, O. Mendoza, C. Morganti,	
C. Houghton, D. Krueger, O. Franza, J. Desai, J. Crop, B. Brock, D. Bradley, C. Bostak, S. Bhimji, and M. Becker	92

(Contents Continued on Back Cover)



Carrizo: A High Performance, Energy Efficient 28 nm APU	
	105
and Error Detection for Tolerance to Within-Die Variation, Voltage Droop, Temperature and Aging	117
	117
A 10ps Time-Resolution CMOS Image Sensor with 2-Tap True-CDS Lock-In Pixels for Fluorescence Lifetime Imaging <i>M</i> -W Seo, K Kagawa, K Yasutomi, Y Kawata, N Teranishi, 7 Li, LA Halin, and S Kawahito.	130
A 160×120-Pixel Analog-Counting Single-Photon Imager with Time-Gating and Self-Referenced Column-Parallel A/D Conversion for Fluorescence Lifetime Imaging	141
A Pen-Pressure-Sensitive Capacitive Touch System Using Electrically Coupled Resonance Pen	155
A 3-Axis Gyroscope for Electronic Stability Control with Continuous Self-Test	168
G. K. Balachandran, V. P. Petkov, T. Mayer, and T. Balslink,	177
A 30 ppm < 80 nJ Ring-Down-Based Readout Circuit for Resonant Sensors	
A Low Power 64 Gb MLC NAND-Flash Memory in 15 nm CMOS Technology	187
M. Sako, Y. Watanabe, T. Nakajima, J. Sato, K. Muraoka, M. Fujiu, F. Kono, M. Nakagawa, M. Masuda,	
K. Kato, Y. Terada, Y. Shimizu, M. Honma, A. Imamoto, T. Araya, H. Konno, T. Okanaga, T. Fujimura, X. Wang, M. Muramoto, M. Kamoshida, M. Kohno, Y. Suzuki, T. Hashiguchi, T. Kobayashi, M. Yamaoka, and R. Yamashita	196
A 128 Gb 3b/cell V-NAND Flash Memory With 1 Gb/s I/O Rate	
HW. Park, DH. Kwak, SW. Park, SM. Yoon, WG. Hahn, JH. Ryu, SW. Shim, KT. Kang, JD. Ihm, IM. Kim,	204
DS. Lee, JH. Cho, MS. Kim, JH. Jang, SW. Hwang, DS. Byeon, HJ. Yang, K. Park, KH. Kyung, and JH. Choi A 28 nm Embedded Split-Gate MONOS (SG-MONOS) Flash Macro for Automotive Achieving 6.4 GB/s Read Throughput by 200 MHz No Wait Read Operation and 2.0 MP/c Write Throughput at Ti of 170°C	204
Y Taito T Kono M Nakano T Saito T Ito K Noguchi H Hidaka and T Yamauchi	213
A 0.6 V, 1.5 GHz 84 Mb SRAM in 14 nm FinFET CMOS Technology With Capacitive Charge-Sharing Write Assist Circuitry	
E. Karl, Z. Guo, J. Conary, J. Miller, YG. Ng, S. Nalam, D. Kim, J. Keane, X. Wang, U. Bhattacharya, and K. Zhang	223
A 14 nm 1.1 Mb Embedded DRAM Macro With 1 ns Access G. Fredeman, D. W. Plass, A. Mathews,	
J. Viraraghavan, K. Reyer, I. J. Knips, I. Miller, E. L. Gerhard, D. Kannambadi, C. Paone, D. Lee, D. J. Kainey, M. Sparling, M. Wholen, S. Burns, P. P. Tummuru, H. Ho, A. Castaro, N. Arnold, P. A. Khan, T. Kirihata, and S. S. Juar	221
A 0.20mm <sup>2</sup> 3nW Signal Acquisition IC for Miniature Sensor Nodes in 65nm CMOS	231
P. Harpe, H. Gao, R. V. Dommele, E. Cantatore, and A. H. M. van Roermund,	241
A NEMS-array control IC for sub-attogram mass sensing applications in 28nm CMOS technology	
A Portable Micro Gas Chromatography System for Lung Cancer Associated Volatile Organic Compound Detection	250
P-K Huang V-M Huang W-C Hsigh Y-I Huang P-H Kuo S-A Yu S-C Lee Y I Tseng W-C Tian and S-S I u	260
An Ultra-Thin Flexible CMOS Stress Sensor Demonstrated on an Adaptive Robotic Gripper	200
Y. Mahsereci, S. Saller, H. Richter, and J. N. Burghartz,	274
A Large-Area Image Sensing and Detection System Based on Embedded Thin-Film Classifiers	
	282
A 90 nm CMOS, $\sigma \mu w$ Power-Proportional Acoustic Sensing Frontend for Voice Activity Detection	202
A 20k-spin Ising Chip to Solve Combinatorial Optimization Problems with CMOS Annealing	<i>L7L</i>
A 79n I/b 80Mb/s Full-Duplex Transceiver and a 42 SuW 100kb/s Super-Regenerative Transceiver for Body Channel	304
Communication	311