

IEEE

MICROWAVE AND WIRELESS COMPONENTS LETTERS.®

A PUBLICATION OF THE IEEE MICROWAVE THEORY AND TECHNIQUES SOCIETY



JULY 2016

VOLUME 26

NUMBER 7

IMWCBJ

(ISSN 1531-1309)

LETTERS

Theory and Numerical Methods

Proof of Perturbational Duality Between Classical Cavities and Planar Resonators With Magnetic Side-Walls	469
. <i>A. Naji and P. A. Warr</i>	

Passive Components and Circuits

Spatial Power Combining and Splitting in Gap Waveguide Technology	472
. <i>R. Maaskant, W. A. Shah, A. U. Zaman, M. Ivashina, and P.-S. Kildal</i>	
A Novel Iris Waveguide Bandpass Filter Using Air Gapped Waveguide Technology	475
. <i>D. Sun and J. Xu</i>	
Low-loss and Broadband G-Band Dielectric Interconnect for Chip-to-Chip Communication	478
. <i>B. Yu, Y. Liu, Y. Ye, X. Liu, and Q. J. Gu</i>	
Millimeter Wave E-Plane Transition From Waveguide to Microstrip Line With Large Substrate Size Related to MMIC Integration	481
. <i>A. U. Zaman, V. Vassilev, P.-S. Kildal, and H. Zirath</i>	
A Novel Dual-Band Bandpass E-plane Filter Using Compact Resonators	484
. <i>J. Y. Jin, X. Q. Lin, and Q. Xue</i>	
Compact Microstrip Dual-Band Quadrature Coupler Based on Coupled-Resonator Technique	487
. <i>C.-F. Chen, S.-F. Chang, and B.-H. Tseng</i>	
Quad-Band Rat-Race Coupler With Suppression of Spurious Pass-Bands	490
. <i>S. Velan, S. Kingsly, M. Kanagasabai, M. G. N. Alsath, Y. Panneer Selvam, and S. Subbaraj</i>	
Compact LTCC Balun With Bandpass Response Based on Marchand Balun	493
. <i>J.-X. Xu, X. Y. Zhang, and X.-L. Zhao</i>	
Comments on “Design of a Microstrip Dual-Band Crossover With Asymmetrical II-Shaped Transmission Lines”	496
. <i>R. Sinha and A. De</i>	
A Compact High-Reliability High-Performance 900-MHz WPD Using GaAs-IPD Technology	498
. <i>T. Qiang, C. Wang, and N.-Y. Kim</i>	
A Compact Half-Mode Substrate Integrated Waveguide Bandpass Filter With Wide Out-of-Band Rejection	501
. <i>Q.-L. Zhang, B.-Z. Wang, D.-S. Zhao, and K. Wu</i>	

Electron Devices and Device Modeling

Ultra-High Tunability of Ba _(2/3) Sr _(1/3) TiO ₃ -Based Capacitors Under Low Electric Fields	504
. <i>A. Ghalem, M. Rammal, L. Huitema, A. Crunteanu, V. Madrangeas, P. Dutheil, F. Dumas-Bouchiat, P. Marchet, C. Champeaux, L. Trupina, L. Nedelcu, and M. G. Banciu</i>	
A Hybrid Pad-Line-Finger De-Embedding Technique for Broadband Modeling of CMOS Transistor	507
. <i>X. S. Loo, K. W. J. Chew, K. S. Yeo, M. Z. Win, and C. C. Boon</i>	

(Contents Continued on Back Cover)



Hybrid and Monolithic RF Integrated Circuits

A 109 GHz CMOS Power Amplifier With 15.2 dBm Psat and 20.3 dB Gain in 65-nm CMOS Technology 510
H. S. Son, J. Y. Jang, D. M. Kang, H. J. Lee, and C. S. Park

Adaptive Envelope Shaping for Low and Medium Power Amplifiers with Dynamic Supply 513
P. L. Gilabert, G. Montoro, N. Ruiz, and J. A. Garcia

An Ultra Compact Watt-Level Ka-Band Stacked-FET Power Amplifier 516
D. P. Nguyen and A.-V. Pham

Design of Broadband Power Amplifiers Based on Resistive-Reactive Series of Continuous Modes 519
W. Shi, S. He, Q. Li, T. Qi, and Q. Liu

Extend the Class-B to Class-J Continuum Mode by Adding Arbitrary Harmonic Voltage Elements 522
Q. Li, S. He, W. Shi, Z. Dai, and T. Qi

A Series of Inverse Continuous Modes for Designing Broadband Power Amplifiers 525
W. Shi, S. He, and Q. Li

Ultra-Low Power Direct-Conversion 16 QAM Transmitter Based on Doherty Power Amplifier 528
D. Jeong, S. Lee, H. Lee, and B. Kim

A 100-GHz 0.21-K NETD 0.9-mW/pixel Charge-Accumulation Super-Regenerative Receiver in 65-nm CMOS 531
G. Feng, C. C. Boon, F. Meng, and X. Yi

A Current-Reused Back-Gate Coupling QVCO Using Transformer Feedback Structure 534
M. Jalalifar and G.-S. Byun

Wide-Locking Range Divide-by-3 Injection-Locked Frequency Divider Through Enhanced 2nd Harmonic 537
S.-L. Jang, T.-C. Kung, and C.-W. Hsue

A Low-Phase-Noise 77-GHz FMCW Radar Transmitter With a 12.8-GHz PLL and a $\times 6$ Frequency Multiplier 540
J.-H. Song, C. Cui, S.-K. Kim, B.-S. Kim, and S. Nam

Measurement Techniques, System Modeling Techniques and Applications

A Passive Wireless Adaptive Repeater for Enhancing the Readout of LC Passive Wireless Sensors 543
L. Dong, L.-F. Wang, and Q.-A. Huang

Sensitivity Improvement of Phase-Noise Measurement of Microwave Oscillators Using IF Delay Line Based Discriminator 546
A. Salehi Barzegar, A. Banai, and F. Farzaneh

Remotely Powered Piezoresistive Pressure Sensor: Toward Wireless Monitoring of Intracranial Pressure 549
M. W. A. Khan, T. Björninen, L. Sydänheimo, and L. Ukkonen
