

ΠΗ
I-68/4e3

IEEE TRANSACTIONS ON ELECTRON DEVICES

A PUBLICATION OF THE IEEE ELECTRON DEVICES SOCIETY



JULY 2014

VOLUME 61

NUMBER 07

IETDAI

(ISSN 0018-9383)

REGULAR PAPERS

Silicon and Column IV Semiconductors Devices

Stability Constraints Define the Minimum Subthreshold Swing of a Negative Capacitance Field-Effect Transistor	<i>A. Jain and M. A. Alam</i>	2235
Stochastic Modeling of Positive Bias Temperature Instability in High- κ Metal Gate nMOSFETs	<i>M. K. Hassan, C.-H. Ho, and K. Roy</i>	2243
Improved Body Effect and Analog Characteristics of n-Channel MOSFET With Lateral Asymmetric Substrate Doping	<i>K.-Y. Na, K.-J. Baek, J.-K. Kim, D. Kim, N.-S. Kim, and Y.-S. Kim</i>	2250
Output-Conductance Transition-Free Method for Improving the Radio-Frequency Linearity of Silicon-on-Insulator MOSFET Circuits	<i>A. Daghighi</i>	2257
A Pseudo-2-D-Analytical Model of Dual Material Gate All-Around Nanowire Tunneling FET	<i>R. Vishnoi and M. J. Kumar</i>	2264
Predictive Simulation and Benchmarking of Si and Ge pMOS FinFETs for Future CMOS Technology	<i>L. Shifren, R. Aitken, A. R. Brown, V. Chandra, B. Cheng, C. Riddet, C. L. Alexander, B. Cline, C. Millar, S. Sinha, G. Yeric, and A. Asenov</i>	2271
Improved Electrothermal Ruggedness in SiC MOSFETs Compared With Silicon IGBTs	<i>P. Alexakis, O. Alatise, J. Hu, S. Jahdi, L. Ran, and P. A. Mawby</i>	2278
A Charge-Trapping Model for the Fast Component of Positive Bias Temperature Instability (PBTI) in High- κ Gate-Stacks	<i>L. Vandelli, L. Larcher, D. Veksler, A. Padovani, G. Bersuker, and K. Matthews</i>	2287
Investigations of Conduction Mechanisms of the Self-Rectifying n ⁺ Si-HfO ₂ -Ni RRAM Devices	<i>D. Lu, Y. Zhao, T. X. Anh, Y. H. Yu, D. Huang, Y. Lin, S.-J. Ding, P.-F. Wang, and M.-F. Li</i>	2294

(Contents Continued on Page 2233)

Increased Multilayer Fabrication and RF Characterization of a High-Density Stacked MIM Capacitor Based on Selective Etching	V. F.-G. Tseng and H. Xie	2302
Germanane: a Low Effective Mass and High Bandgap 2-D Channel Material for Future FETs	R. K. Ghosh, M. Brahma, and S. Mahapatra	2309
Physical Origins of High Normal Field Mobility Degradation in Ge p- and n-MOSFETs With GeO _x /Ge MOS Interfaces Fabricated by Plasma Postoxidation	R. Zhang, X. Yu, M. Takenaka, and S. Takagi	2316
Impact of Correlated RF Noise on SiGe HBT Noise Parameters and LNA Design Implications	X. Jia and G. Niu	2324
Compound Semiconductor Devices		
Nonplanar InGaAs Gate Wrapped Around Field-Effect Transistors	F. Xue, A. Jiang, Y.-T. Chen, Y. Wang, F. Zhou, Y.-F. Chang, and J. Lee	2332
Fabrication of Submicrometer InGaAs/AlAs Resonant Tunneling Diode Using a Trilayer Soft Reflow Technique With Excellent Scalability	M. A. Md Zawawi, K. W. Ian, J. Sexton, and M. Missous	2338
A Continuous Analytical Model for 2-DEG Charge Density in AlGaIn/GaN HEMTs Valid for All Bias Voltages	N. Karumuri, S. Turuvekere, N. DasGupta, and A. DasGupta	2343
Memory Devices and Technology		
A Highly Reliable 2-Bits/Cell Split-Gate Flash Memory Cell With a New Program-Disturbs Immune Array Configuration	L. Fang, J. Gu, B. Zhang, W.-R. Kong, and S.-C. Zou	2350
An 8T Low-Voltage and Low-Leakage Half-Selection Disturb-Free SRAM Using Bulk-CMOS and FinFETs	G. Pasandi and S. M. Fakhraie	2357
High Performance of Fin-Shaped Tunnel Field-Effect Transistor SONOS Nonvolatile Memory With All Programming Mechanisms in Single Device	Y.-R. Jhan, Y.-C. Wu, H.-Y. Lin, M.-F. Hung, Y.-H. Chen, and M.-S. Yeh	2364
Design of Gate-All-Around Silicon MOSFETs for 6-T SRAM Area Efficiency and Yield	Y.-B. Liao, M.-H. Chiang, N. Damrongplasit, W.-C. Hsu, and T.-J. K. Liu	2371
Analytical Modeling of Oxide-Based Bipolar Resistive Memories and Complementary Resistive Switches	S. Ambrogio, S. Balatti, D. C. Gilmer, and D. Ielmini	2378
Thin Film Transistors		
Bidirectional Communication in an HF Hybrid Organic/Solution-Processed Metal-Oxide RFID Tag	K. Myny, M. Rockelé, A. Chasin, D.-V. Pham, J. Steiger, S. Botnaras, D. Weber, B. Herold, J. Ficker, B. van der Putten, G. H. Gelinck, J. Genoe, W. Dehaene, and P. Heremans	2387
A New Definition of the Threshold Voltage for Amorphous InGaZnO Thin-Film Transistors	L. Qiang and R. Yao	2394
Improved Performance of Bottom-Contact Organic Thin-Film Transistor Using Al Doped HfO ₂ Gate Dielectric	W. M. Tang, U. Aboudi, J. Provine, R. T. Howe, and H.-S. P. Wong	2398
Optoelectronics, Displays, and Imaging		
Impact of Charge-Trap Layer Conductivity Control on Device Performances of Top-Gate Memory Thin-Film Transistors Using IGZO Channel and ZnO Charge-Trap Layer	J. Y. Bak, M.-K. Ryu, S. H. K. Park, C.-S. Hwang, and S. M. Yoon	2404
A Theory of Multiplication Noise for Electron Multiplying CMOS Image Sensors	T. Brugière, F. Mayer, P. Fereyre, A. Dominjon, and R. Barbier	2412
Modeling and Design of Photonic Crystal Quantum-Dot Semiconductor Optical Amplifiers	H. Taleb and K. Abedi	2419
Vertical-Injection GaN-Based Light-Emitting Diodes Fabricated With Schottky-Contact Current Blocking Layer	M. Oh and H. Kim	2427
Impact of Current Filaments on the Material and Output Characteristics of GaAs Photoconductive Switches	C. Ma, W. Shi, M. Li, H. Gui, N. Hao, and P. Xue	2432
Plan View and Cross-Sectional View EBIC Measurements: Effect of e-Beam Injection Conditions on Extracted Minority Carrier Transport Properties	O. Marcelot, S. I. Maximenko, and P. Magnan	2437
Spatial Correlation Between Efficiency and Crystal Structure in GaN-Based Light-Emitting Diodes Prepared on High-Aspect Ratio Patterned Sapphire Substrate With Sputtered AlN Nucleation Layer	L.-C. Chang, Y.-A. Chen, and C.-H. Kuo	2443
Dual Gate Indium-Zinc Oxide Thin-Film Transistors Based on Anodic Aluminum Oxide Gate Dielectrics	M. Li, L. Zhou, W. Wu, J. Pang, J. Zou, J. Peng, and M. Xu	2448
New Voltage-Programmed AMOLED Pixel Circuit to Compensate for Nonuniform Electrical Characteristics of LTPS TFTs and Voltage Drop in Power Line	C.-L. Lin, C.-C. Hung, P.-S. Chen, P.-C. Lai, and M.-H. Cheng	2454

Solid-State Power and High Voltage Devices

Design and Experimental Study of 4H-SiC Trenched Junction Barrier Schottky Diodes *N. Ren, J. Wang, and K. Sheng* 2459

A RESURF-Enhanced p-Channel Trench SOI LDMOS With Ultralow Specific ON-Resistance *K. Zhou, X. Luo, Q. Xu, Z. Li, and B. Zhang* 2466

Materials, Processing and Packaging

Nondestructive Measurement of the Residual Stresses in Copper Through-Silicon Vias Using Synchrotron-Based Microbeam X-Ray Diffraction *C. Okoro, L. E. Levine, R. Xu, K. Hummler, and Y. S. Obeng* 2473

Magnetic Wireless Interlayer Transmission Through Perpendicular MTJ for 3-D IC Applications *L.-S. Chang, C.-H. Wang, K.-Y. Dai, K.-H. Shen, M.-J. Tsai, C. J. Lin, and Y.-C. King* 2480

Solid State Device Phenomena

Mobility Measurement in Nanowires Based on Magnetic Field-Induced Current Splitting Method in H-Shape Devices *L. Barbut, F. Jazaeri, D. Bouvet, and J.-M. Sallese* 2486

A Statistical Model for the Headed and Tail Distributions of Random Telegraph Signal Magnitudes in Nanoscale MOSFETs *M.-J. Chen, K.-C. Tu, H.-H. Wang, C.-L. Chen, S.-Y. Lai, and Y.-S. Liu* 2495

High Density Solenoidal Series Pair Symmetric Inductors and Transformers *V. N. R. Vanukuru and A. Chakravorty* 2503

Accurate Fast Capacitance Measurements for Reliable Device Characterization *P. R. Shrestha, K. P. Cheung, J. P. Campbell, J. T. Ryan, and H. Baumgart* 2509

Impact of a Pocket Doping on the Device Performance of a Schottky Tunneling Field-Effect Transistor *S. Guin, A. Chattopadhyay, A. Karmakar, and A. Mallik* 2515

Vacuum Electron Devices

Development and Application of a Nonlinear Beam-Wave Interaction Code SBK2D for Sheet Beam Klystrons *C. Ruan, S. Chen, X. Zhang, C. Zhang, S. Wang, and X. Yang* 2523

Design and Experiment of a 220/420-GHz Gyrotron for Nondestructive Evaluation *W. Fu, X. Guan, C. Chen, X. Li, X. Yuan, and Y. Yan* 2531

Toward Amp-Level Field Emission With Large-Area Arrays of Pt-Coated Self-Aligned Gated Nanoscale Tips *A. A. Fomani, S. A. Guerrero, L. F. Velásquez-García, and A. I. (Tayo) Akinwande* 2538

Computational Design and Optimization of a Magnetron Injection Gun *W. Jiang, Y. Luo, and R. Yan* 2547

Multipactor Effect in a Parallel-Plate Waveguide Partially Filled With Magnetized Ferrite *D. González-Iglesias, B. Gimeno, V. E. Boria, Á. Gómez, and A. Vegas* 2552

Electrostatic Beam Focusing of Carbon Nanotubes Electron Source *G. Ulisse, C. Ciceroni, F. Brunetti, and A. D. Carlo* 2558

Design and Experimental Study of a High-Gain W-Band Gyro-TWT With Nonuniform Periodic Dielectric Loaded Waveguide *R. Yan, Y. Tang, and Y. Luo* 2564

Emerging Technologies and Devices

Simulation of DC and RF Performance of the Graphene Base Transistor *S. Venica, F. Driussi, P. Palestri, D. Esseni, S. Vaziri, and L. Selmi* 2570

BRIEF PAPERS

Modeling of a Parameter to Evaluate Multilevel Operation of Bipolar Oxide Resistive Device *S.-J. Choi, K.-H. Kim, W.-Y. Yang, and S. Cho* 2577

3-D Vertical Dual-Layer Oxide Memristive Devices *S. Gaba, P. Sheridan, C. Du, and W. Lu* 2581

Fast Location of Opens in TSV-Based 3-D Chip Using Simple Resistor Chain *S. Hu, C. Jin, H. Li, R. Li, S. C. Chong, M. C. Jong, E. L. C. Wai, K. H. Teo, M. Je, and P. G. Q. Lo* 2584

Optimized pMOS-Triggered Bidirectional SCR for Low-Voltage ESD Protection Applications *Z. Wang, R.-C. Sun, J. J. Liou, and D.-G. Liu* 2588

The pn Junctions of Epitaxial Germanium on Silicon by Solid Phase Doping *W.-H. Tu, S.-H. Hsu, and C.-W. Liu* 2595

Compact Analytical Drain Current Model of Gate-All-Around Nanowire Tunneling FET *R. Vishnoi and M. J. Kumar* 2599

COMMENTS AND CORRECTIONS

Corrections to "Electro-Optical Modulation Processes in Si-PMOSFET LEDs Operating in the Avalanche Light Emission Mode" *K. Xu, W. Sun, and G. P. Li* 2604