

*Journal of*

# Lightwave Technology

Networks and  
Switching

Systems and  
Subsystems



Fibers and Cables

Active Components

Passive Components

*This Print Collection Contains the Following Issues:*

November 1, 2016	Volume 34	Number 21	JLTEDG
November 15, 2016	Volume 34	Number 22	
December 1, 2016	Volume 34	Number 23	
December 15, 2016	Volume 34	Number 24	



Integrated Optics

Optoelectronics

Sensors

Theory

For the November 1, 2016 issue, see p. 4845 for the Table of Contents.  
 For the November 15, 2016 issue, see p. 5092 for the Table of Contents.  
 For the December 1, 2016 issue, see p. 5349 for the Table of Contents.  
 For the December 15, 2016 issue, see p. 5591 for the Table of Contents.

# Journal of Lightwave Technology

A JOINT IEEE / OSA PUBLICATION

NOVEMBER 1, 2016

VOLUME 34

NUMBER 21

JLTEDG

(ISSN 0733-8724)

## Networks

- Optimal and Robust Secure Beamformer for Indoor MISO Visible Light Communication ..... *S. Ma, Z.-L. Dong, H. Li, Z. Lu, and S. Li* 4988
- Effective Capacity of Coherent POLMUX OWC Impaired by Atmospheric Turbulence and Pointing Errors ..... *M. Z. Hassan, M. J. Hossain, J. Cheng, and V. C. M. Leung* 5007
- On the Unprecedented Scalability of the FISSION (Flexible Interconnection of Scalable Systems Integrated Using Optical Networks) Datacenter ..... *A. Gumaste, A. Kushwaha, T. Das, B. M. K. Bheri, and J. Wang* 5074

## Systems/Subsystems

- An Energy Efficient 56 Gbps PAM-4 VCSEL Transmitter Enabled by a 100 Gbps Driver in 0.25  $\mu\text{m}$  InP DHBT Technology ..... *J. Chen, Z. S. He, T. Lengyel, K. Szczerba, P. Westbergh, J. S. Gustavsson, H. Zirath, and A. Larsson* 4954
- Self-Seeded DWDM Solution for Fronthaul Links in Centralized-Radio Access Network ..... *T. Diallo, A. Pizzinat, F. Saliou, P. Chanclou, G. Simon, and C. Aupetit-Berthelemot* 4965
- Distributive FIR-Based Chromatic Dispersion Equalization for Coherent Receivers ..... *C. S. Martins, F. P. Guiomar, S. B. Amado, R. M. Ferreira, S. Ziaie, A. Shahpari, A. L. Teixeira, and A. N. Pinto* 5023
- High-Efficiency Endpoint Detection in Optical Fiber Perimeter Security ..... *X. Huang, Y. Wang, K. Liu, T. Liu, C. Ma, and M. Tian* 5049
- On Probabilistic Shaping of Quadrature Amplitude Modulation for the Nonlinear Fiber Channel ..... *T. Fehenberger, A. Alvarado, G. Böcherer, and N. Hanik* 5063

## Fibers/Cables

- Slightly Tapered Optical Fiber With Dual Inner Air-Cavities for Simultaneous Refractive Index and Temperature Measurement ..... *J. Liu, D. N. Wang, and L. Zhang* 4872
- Fiber-Optic Anemometer Based on Bragg Grating Inscribed in Metal-Filled Microstructured Optical Fiber ..... *J. Wang, Z.-Y. Liu, S. Gao, A. P. Zhang, Y.-H. Shen, and H.-Y. Tam* 4884
- Design of Palladium-Coated Long-Period Fiber Grating for Hydrogen Sensing ..... *N. Basumallick, P. Biswas, R. M. Carter, R. R. J. Maier, S. Bandyopadhyay, K. Dasgupta, and S. Bandyopadhyay* 4912

(Contents Continued on Page 4846)

JOURNAL OF LIGHTWAVE TECHNOLOGY (ISSN 0733-8724) is published semimonthly by the Institute of Electrical and Electronics Engineers, Inc. Responsibility for the contents rests upon the authors and not upon the IEEE, the Society/Council, or its members. **IEEE Corporate Office:** 3 Park Avenue, 17th Floor, New York, NY 10016-5997. **IEEE Operations Center:** 445 Hoes Lane, Piscataway, NJ 08854-4141. **NJ Telephone:** +1 732 981 0060. **Price/Publication Information:** Individual copies: IEEE Members \$20.00 (first copy only), nonmembers \$427.00 per copy. (Note: Postage and handling charge not included.) Member and nonmember subscription prices available upon request. Available in microfiche and microfilm. **Copyright and Reprint Permissions:** Abstracting is permitted with credit to the source. Libraries are permitted to photocopy for private use of patrons, provided the per-copy fee of \$31.00 is paid through the Copyright Clearance Center, 222 Rosewood Drive, Danvers, MA 01923. For all other copying, reprint, or republication permission, write to Copyrights and Permissions Department, IEEE Publications Administration, 445 Hoes Lane, Piscataway, NJ 08854-4141. Copyright © 2016 by the Institute of Electrical and Electronics Engineers, Inc. All rights reserved. **Postmaster:** Send address changes to JOURNAL OF LIGHTWAVE TECHNOLOGY, IEEE, 445 Hoes Lane, Piscataway, NJ 08854-4141. GST Registration No. 125634188. CPC Sales Agreement #40013087. Return undeliverable Canada addresses to: Pitney Bowes IMEX, P.O. Box 4332, Stanton Rd., Toronto, ON M5W 3J4, Canada. IEEE prohibits discrimination, harassment and bullying. For more information visit <http://www.ieee.org/nondiscrimination>. Printed in U.S.A.

---

Fiber Fabry–Pérot Interferometer for Measurement of Gas Pressure and Temperature . . . . .	4920
. . . . . <i>B. Xu, Y. M. Liu, D. N. Wang, and J. Q. Li</i>	
Filtering Characteristics and Applications of Photonic Crystal Fibers Being Selectively Infiltrated With One Aluminum Rod . . . . .	4972
. . . . . <i>H. Chen, S. Li, M. Ma, Y. Liu, M. Shi, Q. Liu, and T. Cheng</i>	
Study of Radiation Effects on Er <sup>3+</sup> -Doped Nanoparticles Germano-Silica Fibers . . . . .	4981
. . . . . <i>B. H. Babu, N. Ollier, I. Savelli, H. E. Hamzaoui, A. Pastouret, B. Poumellec, M. Bouazaoui, L. Bigot, and M. Lancry</i>	
Design of Arbitrary Shape Higher Order Mode Electric Field in Optical Fibers for High Power Applications . . . . .	5056
. . . . . <i>C. A. Thraskias and A. C. Boucouvalas</i>	
<b>Integrated Optics/Optoelectronics</b>	
Temperature Self-Compensated Optical Waveguide Biosensor Based on Cascade of Ring Resonator and Arrayed Waveguide Grating Spectrometer . . . . .	4856
. . . . . <i>J. Zou, Z. Le, and J.-J. He</i>	
Experimental Demonstration of Directive Si <sub>3</sub> N <sub>4</sub> Optical Leaky Wave Antennas With Semiconductor Perturbations . . . . .	4864
. . . . . <i>Q. Zhao, C. Guclu, Y. Huang, F. Capolino, and O. Boyraz</i>	
An Approach for Increasing User Capacity of OCDMA System Based on Vernier Effect . . . . .	4877
. . . . . <i>D. Jia, C. Du, Z. Ji, H. Zhang, T. Liu, and Y. Zhang</i>	
Bandwidth-Agile Transparency of the Second Mode in a Periodically Corrugated Waveguide With an Arbitrary Wall Profile . . . . .	4890
. . . . . <i>Y.-X. Fan, A. Bibi, L.-L. Xu, D. Xu, T.-Q. Sang, and Z.-Y. Tao</i>	
Study of SiO <sub>x</sub> (1 < x < 2) Thin-Film Optical Waveguides . . . . .	4926
. . . . . <i>E. G. Lizarraga-Medina, D. Salazar, G. V. Vázquez, R. Salas-Montiel, N. Nedev, and H. Márquez</i>	
A Broadband Optical Modulator Based on a Graphene Hybrid Plasmonic Waveguide . . . . .	4948
. . . . . <i>X. Chen, Y. Wang, Y. Xiang, G. Jiang, L. Wang, Q. Bao, H. Zhang, Y. Liu, S. Wen, and D. Fan</i>	
<b>Sensors</b>	
Hot Cavity Optical Fiber Fabry–Perot Interferometer as a Flow Sensor With Temperature Self-Calibrated . . . . .	5044
. . . . . <i>B. Zhou, H. Jiang, C. Lu, and S. He</i>	
<b>Theory</b>	
Flat-Top Supercontinuum and Tunable Femtosecond Fiber Laser Sources at 1.9–2.5 μm . . . . .	4847
. . . . . <i>D. Klimentov, N. Tolstik, V. V. Dvoyrin, R. Richter, and I. T. Sorokina</i>	
Narrow Spectral Width FP Lasers for High-Speed Short-Reach Applications . . . . .	4898
. . . . . <i>J. Fu, Y. Xi, X. Li, and W.-P. Huang</i>	
High-Power Single-Frequency 1336 nm Raman Fiber Amplifier . . . . .	4907
. . . . . <i>L. Zhang, H. Jiang, X. Yang, X. Gu, and Y. Feng</i>	
Laser Linewidth and Phase Noise Evaluation Using Heterodyne Offline Signal Processing . . . . .	4933
. . . . . <i>T. Sutuli, R. C. Figueiredo, and E. Conforti</i>	
Polarimetric Multilongitudinal Mode Fiber Laser for Simultaneous Measurement of Strain and Temperature . . . . .	4941
. . . . . <i>X. Yu, X. Dong, X. Chen, J. Zhang, and S. Liu</i>	
Grating-Assisted Microcylinder Surface-Emitting Laser . . . . .	4999
. . . . . <i>X. Ma, Q. Chen, Q. Lu, and W. Guo</i>	
Simple and Accurate Fluorescence Lifetime Measurement Scheme Using Traditional Time-Domain Spectroscopy and Modern Digital Signal Processing . . . . .	5033
. . . . . <i>A. Zareanborji, H. Yang, G. E. Town, Y. Luo, and G.-D. Peng</i>	

---

About the Cover: (a) Schematic representation of the experimental setup utilized for the magnetic field power coupling measurements (b) Guiding cores allocation, using white light injection. The arrow shows the direction of the applied magnetic field, when is aligned with two outer, opposite cores. For more information, please see “Intercore Coupling Effects in Multicore Optical Fiber Tapers Using Magnetic Fluid Out-Claddings,” by Tagoudi, *et al.*, which begins on p. 5561.

---