

THERMAL ENGINEERING

Pleiades
Publishing Group
Over
50 years
in the service of
science and education

Editor-in-Chief
Aleksey V. Dedov

<https://pleiades.online>
<https://link.springer.com>




PLEIADES GROUP OF COMPANIES

Distributed by **SPRINGER NATURE**




12 articles in this issue

Gas Hydrate Energy Technologies: Problems and Achievements




GENERAL ENERGY ISSUES | 27 January 2026 | Pages: 993 - 1033

Simulation of Thermohydrodynamic Processes during an SBO Accident with the Externally Cooled Vessel of a VVER-I Integral Small Modular Reactor




NUCLEAR POWER PLANTS | 27 January 2026 | Pages: 1034 - 1041

The Influence of Temperature Conditions at the Metallic Melt Layer Boundaries on the Heat Flux Focusing in a Stratified Molten Corium Pool during a Severe Accident in Nuclear Power Facilities




NUCLEAR POWER PLANTS | 27 January 2026 | Pages: 1042 - 1050

Corrosion Product Generation Processes in the Circuits of Nuclear Power Facilities



NUCLEAR POWER PLANTS | 27 January 2026 | Pages: 1051 - 1060

Numerical Simulation of Hydrodynamic Effects of Internal Structural Parameters in a Steam-Water Mixing Heater



STEAM-TURBINE, GAS-TURBINE, AND COMBINED-CYCLE PLANTS AND THEIR AUXILIARY EQUIPMENT

27 January 2026 | Pages: 1061 - 1072

27 January 2026 | Pages: 1073 - 1089

27 January 2026 | Pages: 1090 - 1100

27 January 2026 | Pages: 1101 - 1107

27 January 2026 | Pages: 1108 - 1117

A schematic diagram of a water meter assembly. It shows a vertical pipe with a meter body. Component 1 is the top inlet/outlet. Component 2 is the meter body. Component 3 is the bottom outlet. Component 4 is a horizontal pipe section. Component 5 is a valve or stopcock. Component 6 is a small pipe or fitting at the bottom.

STEAM BOILERS, POWER FUEL, BURNERS, AND AUXILIARY BOILER EQUIPMENT | 27 January 2026
Pages: 1118 - 1124

The diagram shows a cross-section of an ITD structure. On the left is a ZnO layer with a thickness of 10 nm, and on the right is a Si layer with a thickness of 10 nm. The ZnO layer is divided into four sub-layers with energy levels E_v , E_g , E_c , and E_v . The Si layer is divided into two sub-layers with energy levels E_v and E_c . The energy levels are labeled E_v , E_g , E_c , and E_v for the ZnO layer and E_v and E_c for the Si layer. The energy levels are labeled E_v , E_g , E_c , and E_v for the ZnO layer and E_v and E_c for the Si layer. The energy levels are labeled E_v , E_g , E_c , and E_v for the ZnO layer and E_v and E_c for the Si layer.

RENEWABLE ENERGY SOURCES AND HYDROPOWER | 27 January 2026 | Pages: 1125 - 1129

Erratum to: Study of Heating and Evaporation of Rotating Graphene Nanofluid under the Influence of Solar Radiation

